

150 PSI OIL DISCHARGE HOSE

THE T650AH SERIES IS AN 150 PSI OIL DISCHARGE HOSE DESIGNED FOR USE ON TRUCKS, DOCKS OR BARGES WHERE A SOFT WALL HOSE IS REQUIRED.



Cover:

Red CR – abrasion, ozone and hydrocarbon resistant.

Reinforcement:

Spiraled high tensile textile cords with embedded static wire.

Tube:

Black conductive NBR.

Working Pressure:

Constant Pressure – 10 Bar (150 PSI)

Temperature Range:

-22°F (-30°C) to 176°F (+80°C)

Branding:

ALFAGOMMA – ITALY T650 10 BAR (150 PSI) – PETROLEUM DELIVERY (in yellow letters)

COUPLING SUGGESTIONS

Quick-Acting or combination nipples attached with bands.

Nominal Specifications						
Series	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Max Rec. WP (PSI)	Weight (lbs./ft.)
T650AH150	1 1/2	38	1.97	50	150	0.77
T650AH200	2	51	2.40	61	150	0.82
T650AH300	3	76	3.46	88	150	1.42
T650AH400	4	102	4.49	114	150	1.92

GEORGIA
3400 Town Point Dr.
Suite 130
Kennesaw, GA 30144

OHIO
2611 Thunderhawk Ct.
Dayton, OH 45414

(800) 344-0150 phone
(937) 454-2086 fax
sales@ushoseco.com
www.USHOSECO.com

PETROLEUM