

2400 WET EXHAUST - SAE J2006

A SOFT WALL HOSE DESIGNED FOR USE AS A STRAIGHT CONNECTION IN WET EXHAUST SYSTEMS ON MARINE GASOLINE OR DIESEL ENGINES. PROVIDING A WORKING PRESSURE RANGE FROM 50 TO 150 PSI, THE 2400 CAN BE USED IN OTHER MARINE APPLICATIONS SUCH AS DRAINS, IN REPLACEMENT OF METAL PIPING AND VIBRATION ABSORPTION. **NOT DESIGNED FOR VACUUM SERVICE.**



Oil Resistance: Medium to Medium-High
 Construction:
 Tube: NBR/SBR blend
 Cover: CR/NBR blend
 Reinforcement: Tire Cord
 Temperature Range: 0°F to +212°F
 -18°C to +100°C

Product Number 12 Feet	Product Number 60 Feet	Nominal I.D.		Nominal O.D.		Plies	Working Pressure		Min. Bend Radius		Weight		Std. Case
		(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)	
16240007512▲	16240007560▲	3/4	19.05	1.25	31.75	2	150	1.03	n/a	n/a	0.51	0.76	2
16240008712	16240008760	7/8	22.23	1.38	35.05	2	150	1.03	n/a	n/a	0.58	0.86	2
16240010012	16240010060	1	25.40	1.50	38.10	2	150	1.03	n/a	n/a	0.60	0.89	2
16240010612▲	16240010660▲	1-1/16	26.99	1.56	39.62	2	150	1.03	n/a	n/a	0.65	0.97	2
16240011212▲	16240011260▲	1-1/8	28.58	1.63	41.40	2	150	1.03	n/a	n/a	0.71	1.06	2
16240012512	16240012560	1-1/4	31.75	1.75	44.45	2	150	1.03	n/a	n/a	0.74	1.10	2
16240013112▲	16240013160▲	1-5/16	33.34	1.81	45.97	2	150	1.03	n/a	n/a	0.77	1.15	2
16240013712	16240015060	1-3/8	34.93	2.08	52.83	2	150	1.03	n/a	n/a	0.82	1.22	2
16240015012	16240015060	1-1/2	38.10	2.20	55.88	2	150	1.03	n/a	n/a	0.88	1.31	2
16240016212	16240016260	1-5/8	41.28	2.33	59.18	2	150	1.03	n/a	n/a	0.93	1.38	2
16240017512▲	16240017560▲	1-3/4	44.45	2.45	62.23	2	150	1.03	n/a	n/a	0.94	1.40	2
16240018712	16240018760	1-7/8	47.63	2.57	65.28	2	150	1.03	n/a	n/a	1.05	1.56	2
16240020012	16240020060	2	50.80	2.70	68.58	2	100	0.69	n/a	n/a	1.11	1.65	2
16240021212▲	16240021260▲	2-1/8	53.98	2.82	71.63	2	100	0.69	n/a	n/a	1.16	1.73	1
16240022512▲	16240022560▲	2-1/4	57.15	2.95	74.93	2	100	0.69	n/a	n/a	1.22	1.82	1
16240023712	16240023760	2-3/8	60.33	3.07	77.98	2	100	0.69	n/a	n/a	1.28	1.90	1
16240025012	16240025060	2-1/2	63.50	3.20	81.28	2	100	0.69	n/a	n/a	1.33	1.98	1
16240026212▲	16240026260▲	2-5/8	66.68	3.33	84.58	2	100	0.69	n/a	n/a	1.39	2.07	1
16240027512▲	16240027560▲	2-3/4	69.85	3.43	87.12	2	100	0.69	n/a	n/a	1.44	2.14	1
16240028712▲	16240028760▲	2-7/8	73.03	3.57	90.68	2	100	0.69	n/a	n/a	1.50	2.23	1
16240030012	16240030060	3	76.20	3.70	93.98	2	100	0.69	n/a	n/a	1.56	2.32	1
16240032512▲	16240032560▲	3-1/4	82.55	3.95	100.33	2	100	0.69	n/a	n/a	1.62	2.41	1
16240035012	16240035060	3-1/2	88.90	4.20	106.68	2	100	0.69	n/a	n/a	1.73	2.57	1
16240037512▲	16240037560▲	3-3/4	95.25	4.45	113.03	2	100	0.69	n/a	n/a	1.84	2.74	1
16240040012	16240040060	4	101.60	4.70	119.38	2	100	0.69	n/a	n/a	1.96	2.92	1
16240045012	16240045060	4-1/2	114.30	5.20	132.08	2	100	0.69	n/a	n/a	2.18	3.24	1
16240050012▲	16240050060▲	5	127.00	5.70	144.78	2	100	0.69	n/a	n/a	2.41	3.59	1
16240055012▲	16240055060▲	5-1/2	139.70	6.20	157.48	2	100	0.69	n/a	n/a	2.63	3.91	1
16240055612▲	16240055660▲	5-9/16	141.29	6.26	159.00	2	100	0.69	n/a	n/a	2.66	3.96	1
16240060012▲	16240060060▲	6	152.40	6.76	159.00	2	100	0.69	n/a	n/a	2.86	4.26	1
16240066212▲		6-5/8	168.28	7.38	187.45	4	100	0.69	n/a	n/a	4.40	6.55	1
16240070012▲		7	177.80	7.75	196.85	4	100	0.69	n/a	n/a	4.54	6.76	1
16240080012▲		8	203.20	8.75	222.25	4	85	0.59	n/a	n/a	5.25	7.81	1
16240086212▲		8-5/8	219.08	9.38	238.25	4	85	0.59	n/a	n/a	5.64	8.39	1
16240001012▲		10	254.00	10.75	273.05	4	75	0.52	n/a	n/a	6.49	9.66	1
16240010712▲		10-3/4	273.05	11.50	292.10	4	70	0.48	n/a	n/a	7.05	10.49	1
16240012012▲		12	304.80	12.75	323.85	4	60	0.41	n/a	n/a	7.83	11.65	1
16240012712▲		12-3/4	323.85	13.50	342.90	4	50	0.34	n/a	n/a	8.26	12.29	1

▲ = Make To Order (MTO)
 n/a = Not Applicable

GEORGIA
 3400 Town Point Dr.
 Suite 130
 Kennesaw, GA 30144

OHIO
 2611 Thunderhawk Ct.
 Dayton, OH 45414

(800) 344-0150 phone
(937) 454-2086 fax
sales@ushoseco.com
www.USHOSECO.com

AUTO/MARINE/COOLANT