

3859 HOT TAR & ASPHALT HOSE

DESIGNED FOR THE
TRANSFER OF TAR,
ASPHALT, HOT OILS AND
OTHER HIGH
TEMPERATURE
PETROLEUM-BASED
PRODUCTS.

**NOT FOR USE WITH
BIOFUELS**



Construction:

Tube: Black high grade nitrile rubber
Reinforcement: Plies of polyester tire cord with helix wire
Cover: Smooth black abrasion resistant nitrile
Length: 100 ft.
Temperature Range: -40° (-40°C) to +350°F (+177°C)
(Intermittent service only)

Not for use with BioFuels

When coupling chemical and higher risk hoses, Novaflex® recommends the use of crimp couplings using interlocking crimp ferrules.

Part No.	I.D.	O.D.	Plies	MBR (in)	WP psi	VAC HG	WT LBS/FT
3859BT-02000-00	2	2.72	2	6	150	30"	1.18
3859BT-02500-00	2½	3.24	2	7	150	30"	1.56
3859BT-03000-00	3	3.79	2	9	150	30"	1.84
3859BT-04000-00	4	4.79	2	12	150	30"	2.39

SPECIALTY

GEORGIA
3400 Town Point Dr.
Suite 130
Kennesaw, GA 30144

OHIO
2611 Thunderhawk Ct.
Dayton, OH 45414

(800) 344-0150 phone
(937) 454-2086 fax
sales@ushoseco.com
www.USHOSECO.com