

A1687 SERIES - 800 PSI PVC/POLYURETHANE BLEND REINFORCED SPRAY HOSE

THE A1687 SERIES SPRAY HOSE HAS A UNIQUE PVC/POLYURETHANE BLENDED CORE WHICH PROVIDES EXCELLENT RESISTANCE TO HYDROCARBON-BASED TREE SPRAY, LAWN CARE AND PEST CONTROL CHEMICALS. THIS PRODUCT IS REINFORCED WITH HIGH TENSILE STRENGTH YARN AND A PVC RIBBED COVER PROVIDES ABRASION RESISTANCE.



Construction:

- Tube — Black PVC/polyurethane blend.
- Reinforcement — High tensile strength yarn two-pass spiral construction.
- Cover — Ribbed PVC.

Applications:

- Tree and orchard spraying.
- Agricultural spraying.
- Commercial weed spraying.

Service Temperature Range:

+15°F (-10°C) to +160°F (+70°C)

Features:

- Extremely tough and kink resistant.
- PVC/polyurethane blended core — provides better chemical resistance than comparable all-PVC hoses.
- Ribbed cover provides excellent abrasion-resistance.
- 800 PSI working pressure.
- Pin-pricked cover vents vapor . . . helps prevent ballooning.
- Silicone-free.
- One-piece lengths.
- Phthalate Free!

Nominal Specifications

Series No.	Size Code	Nominal ID		Nominal OD		Max. Working Pressure† (PSI)		Standard Coil Lengths	Approx. Wt. per Pkg.	
		(In)	(mm)	(In)	(mm)	@ 70°F (20°C)	@ 122°F (50°C)		300ft. Coil	400ft. Coil
A1687	06	3/8	9.5	.650	16.5	800	450	300 or 400 ft.	41 lbs.	54 lbs.
A1687	08	1/2	12.7	.850	21.6	800	450	300 or 400 ft.	68 lbs.	90 lbs.
A1687	10	5/8	15.9	1.030	26.2	800	400	300 ft.	96 lbs.	—
A1687	12	3/4	19.1	1.170	29.7	800	400	300 ft.	126 lbs.	—

† Note: Working Pressure decreases as temperature increases. Pressure ratings can only be obtained with proper coupling procedures.

REINFORCED SPRAY

GEORGIA
3400 Town Point Dr.
Suite 130
Kennesaw, GA 30144

OHIO
2611 Thunderhawk Ct.
Dayton, OH 45414

(800) 344-0150 phone
(937) 454-2086 fax
sales@ushoseco.com
www.USHOSECO.com