




BLACK HEATER - STANDARD

BLACK HEATER HOSE FEATURES A KINK-RESISTANT EPDM TUBE AND COVER THAT RESIST CRACKING AND WEATHER CHECKING ALL WHILE WITHSTANDING THE ABUSE OF CORROSIVE ADDITIVES, OZONE AND ABRASION. THE MULTI-SPIRAL POLYESTER IN THIS HOSE IS REINFORCED TO MAINTAIN ITS FLEXIBILITY EVEN IN EXTREME APPLICATION TEMPERATURES.



<p>RESISTANCE</p> <div style="display: flex; justify-content: space-around;">    </div> <p>Abrasion Coolant Ozone</p> <p>BRANDING: 4709 Thermoid (Size) Heater Hose Made In USA</p> <p>COVER COLOR: Black</p>	<p>CONSTRUCTION</p> <p>TUBE: EPDM, ARPM - Class C</p> <ul style="list-style-type: none"> • High Temperature Resistant <p>COVER: EPDM, ARPM - Class C</p> <ul style="list-style-type: none"> • High Temperature Resistant • Cracking and Weathering Resistant <p>REINFORCEMENT: 2-Spiral Polyester Yarn</p> <ul style="list-style-type: none"> • Provides a Working Pressure Range from 25 to 35 psi, Depending on the I.D. • Easier to Route Assemblies • Easier to Coil and Handle • Less Susceptible to Premature Failure than Braided Hose if Subjected to Torque • Maintains its Flexibility 	<p>TEMPERATURE RANGE: -40°F to +200°F, -40°C to +93°C</p> <ul style="list-style-type: none"> • Still Flexible even in Extreme Temperatures <p>PACKAGING: Reels, 50 ft. Lengths</p> <ul style="list-style-type: none"> • 700 ft. Reels • Over 80% One Piece Reels • Less Scrap • Most Footage per Reel vs. Competition <p>PRESSURELESS CURE SYSTEM</p> <ul style="list-style-type: none"> • Minimal Cast (Natural Curvature of the Hose) • Extends the Life of the Rubber Compounds <p>AIR MANDREL MANUFACTURING PROCESS</p> <ul style="list-style-type: none"> • No Internal Contamination of the Inside Diameter Due to the Lubricant • Eliminates the Need for Customers to Flush the Hose
---	--	---

Product Number	Packaging	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
		Reels (ft.)	(inches)	(mm)	(inches)		(mm)	(psi)	(Mpa)	(inches)	(mm)	(lb/ft)
00470908199	700	½	12.70	0.81	20.64	2	35	0.24	3.00	76.20	0.16	0.24
00470910199	700	⅝	15.88	0.88	22.23	2	35	0.24	3.75	95.25	0.20	0.30
00470912199	700	¾	19.05	1.03	26.19	2	35	0.24	4.50	114.30	0.23	0.34
00470916199	700	1	25.40	1.34	34.13	2	25	0.17	7.00	177.80	0.39	0.58
50 ft. Lengths												
00470908151	1 per carton	½	12.70	0.81	20.64	2	35	0.24	3.00	76.20	0.16	0.24
00470910151	1 per carton	⅝	15.88	0.88	22.23	2	35	0.24	3.75	95.25	0.20	0.30
00470912151	1 per carton	¾	19.05	1.03	26.19	2	35	0.24	4.50	114.30	0.23	0.34
00470916151	1 per carton	1	25.40	1.34	34.13	2	25	0.17	7.00	177.80	0.39	0.58

AUTO/MARINE/COOLANT

GEORGIA
3400 Town Point Dr.
Suite 130
Kennesaw, GA 30144

OHIO
2611 Thunderhawk Ct.
Dayton, OH 45414

(800) 344-0150 phone
(937) 454-2086 fax
sales@ushoseco.com
www.USHOSECO.com