

COBRA FUEL OIL DELIVERY

THE COBRA FUEL OIL HOSE IS DESIGNED FOR THE TRANSFER OF A WIDE VARIETY OF FUELS, OILS, AND OTHER PETROLEUM-BASED PRODUCTS FOR HOME DELIVERY, MARINE, COMMERCIAL AND INDUSTRIAL SERVICE. THE UNIQUE SPIRAL CONSTRUCTION ADDS STRENGTH AND FLEXIBILITY TO MAKE IT EASY TO HANDLE & KINK RESISTANT. A SMOOTH, DURABLE COVER RESISTS OIL AND ABRASION AND PROVIDES EXCELLENT DRAG RESISTANCE.



RESISTANCE



BRANDING: Thermoid Fuel Oil Hose WP
250 PSI Made In USA Month/Year

COVER COLOR: Red

NOTE: A static wire is included on all sizes as a safety precaution.

Compatible fuels are kerosene, diesel, Biodiesel and Biodiesel blends (based on biodiesel fuel equivalent to ASTM D 6751).

For use in dedicated service only with compatible fuels. No alternating fuel types.

CONSTRUCTION

TUBE: Nitrile, ARPM - Class A

- High Oil Resistant
- Designed to Handle a Variety of Fuel Oils
- Water Resistant

COVER: Nitrile Blend, ARPM - Class A

- High Oil Resistant
- Abrasion Resistant
- Heat Resistant

REINFORCEMENT:

- Polyester Reinforcement
- Provides a Working Pressure of 250 psi
- More Flexible than Braid Reinforced Hose
- Easier to Route Assemblies
- Less Susceptible to Premature Failure than Braided Hose if Subjected to Torque
- Kink Resistant

TEMPERATURE RANGE:

- Fuel Oils -40°F to +150°F, -40°C to +70°C
- Gasoline/Gasoline Blends -40°F to +104°F, -40°C to +40°C

**Use in Gasoline or Ethanol Blend Applications Above +104°F (+40°C) is Not Recommended.*

PACKAGING: Reels, Coupled and Uncoupled Lengths

STATIC WIRE, ALL SIZES

- Safety - Grounds the Hose

MOLDED COVER PROCESS

- Showroom Quality
- Dust Free

REELS (THERMOCURE)

Product Number	Packaging Reels (ft.)	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
		(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
22564642662	300-500*	1	25.40	1.50	38.10	4	250	1.72	7.00	177.80	0.47	0.70
22564802662	300-450*	1-¼	31.75	1.78	45.24	4	250	1.72	8.75	222.25	0.59	0.88
22564882662	300-450*	1-¾	34.93	1.88	47.63	4	250	1.72	9.25	234.95	0.65	0.97
22564962662	250-350*	1-½	38.10	2.09	53.18	4	250	1.72	10.50	266.70	0.80	1.19

Note: A static wire is included on all sizes as a safety precaution

*Compatible fuels are kerosene, diesel, Biodiesel and Biodiesel blends (based on biodiesel fuel equivalent to ASTM D 6751. For use in dedicated service only with compatible fuels. No alternating fuel types.

GEORGIA
3400 Town Point Dr.
Suite 130
Kennesaw, GA 30144

OHIO
2611 Thunderhawk Ct.
Dayton, OH 45414

(800) 344-0150 phone
(937) 454-2086 fax
sales@ushoseco.com
www.USHOSECO.com