

ELEXCOR 5

ONE-WIRE BRAID HYDRAULIC HOSE FOR MEDIUM PRESSURE SERVICE IN PETROLEUM-BASED OIL IMPULSE APPLICATIONS: GASOLINE, LUBE OIL, FUEL LINES AND OIL FOR BIODIESEL. CAN ALSO BE USED FOR AIR BRAKES, POWER STEERING, FUEL FILTERS, TURBOCHARGER OIL SUPPLIES, TILT CAB CYLINDERS, TRANSMISSION COOLANT, ENGINE COOLANT AND FILTRATION LINES.



Construction:

Tube - Oil-resistant synthetic rubber.

Reinforcement - One high tensile steel braid.

Cover - Polyester textile braid.

Branding – ALFAGOMMA FLEXOR 5 ID ...WP ...MPa (...PSI) SAE 100 R5*

TR5 – One-wire braid-reinforced

Meets or exceeds SAE 100 R5

SAE J1402 DOT All FM VSS 106

Note: Hose cover does not need to be removed before attaching couplings.

Temperature Range: -40°F (-40°C) to 212°F (100°C) constant operation.

Maximum operating temperature: 257°F (125°C). Air maximum temperature: 160°F (70°C).

Note: Operating temperatures in excess of 212°F (100°C) may materially reduce the life of the hose.

Nominal Specifications

Series Number	Size Code	Nominal ID		Nominal OD		Max. Working [†]	Min. Bend. Radius		Approx	Coupling Recommendations	
						Pressure (psl)			Approx. Weight (lbs./ft.)	Two-Piece Couplings	
		(in.)	(mm)	(in.)	(mm)		(in.)	(mm)		Ferrule Non-Skive	Insert Non-Skive
TR5	04	3/16	5	0.52	13.2	3,000	3.0	76	0.15	AF3-03	A-03XX
TR5	05	1/4	6	0.58	14.8	3,000	3.4	86	0.18	AF3-04	A-04XX
TR5	06	5/16	8	0.68	17.3	2,250	4.1	102	0.23	AF3-05	A-05XX
TR5	08	13/32	11	0.77	19.5	2,000	4.7	117	0.30	AF3-06	A-06XX
TR5	10	1/2	13	0.92	23.4	1,750	5.6	140	0.38	AF3-08	A-08XX
TR5	12	5/8	16	1.08	27.4	1,500	6.6	165	0.45	AF3-10	A-10XX
TR5	16	7/8	22	1.24	31.4	800	7.5	187	0.48	AF3-12	A-14XX
TR5	20	1 1/8	29	1.50	38.1	625	9.2	229	0.57	AF3-16	A-18XX
TR5	24	1 3/8	35	1.75	44.5	500	10.7	267	0.71	AF3-20	A-22XX
TR5	32	1 13/16	46	2.22	56.4	350	13.5	337	0.91	AS1-32*	A-29XX

† Minimum burst pressure 4-to-1 safety factor.

*Do Not Skive

GEORGIA 3400 Town Point Dr. Suite 130 Kennesaw, GA 30144