

# FUEL LINE SAE 30R7

## VAPOR EMISSION & CRANKCASE VENTILATION

A DURABLE, AFTERMARKET STANDARD HOSE USED FOR CONVEYING MOST AUTOMOBILE, TRUCK AND BUS FUEL. THIS HOSE IS IDEAL FOR EQUIPMENT, WHOLESALERS, AFTERMARKET PACKAGERS AND AUXILIARY TANK MANUFACTURERS. IT PROVIDES SUPERIOR SERVICE AND REMAINS FLEXIBLE AND RESISTANT TO OIL, GREASE, OZONE AND UNDER-HOOD ENGINE TEMPERATURES.



#### RESISTANCE



**BRANDING:** Size SAE 30R7-KX Date Made In USA

**COVER COLOR:** Black

Not recommended for recirculating fuel systems. Product conforms to all SAE 30R7 requirements for non-recirculating systems.

#### CONSTRUCTION

**TUBE:** Nitrile, ARPM - Class A  
• Ozone Resistant

**COVER:** Nitrile Blend, ARPM - Class B  
• Heat Resistant  
• Ozone Resistant

**REINFORCEMENT:** 2-Spiral Polyester Yarn  
• 50 psi Regardless of I.D.  
• More Flexible than Braid Reinforced Hose  
• Easier to Route Assemblies  
• Easier to Coil and Handle  
• Less Susceptible to Premature Failure than Braided Hose if Subjected to Torque

#### TEMPERATURE RANGE: -40°F to +257°F, -40°C to +125°C

• Still Flexible even in Extreme Temperatures

#### PACKAGING: Coils, 25 ft. and 50 ft.; Reels, 250 ft. and 700 ft.

• Over 80% One Piece Reels  
• Less Scrap  
• Most Footage per Reel vs. Competition

#### SIMILAR TO SAE 30R7 SPECIFICATION

• Meets or Exceeds Nearly All SAE Requirements

#### PRESSURELESS CURE SYSTEM

• Minimal Cast (Natural Curvature of the Hose)  
• Extends the Life of the Rubber Compounds

Product Number	Packaging	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight		
		Reels (ft.)	(inches)	(mm)	(inches)		(mm)	(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
00667503299	700		3/16	4.76	0.41	10.32	2	50	0.34	1.25	31.75	0.07	0.10
00667504299	700		1/4	6.35	0.50	12.70	2	50	0.34	1.50	38.10	0.09	0.13
00667505299	700		5/16	7.94	0.56	14.29	2	50	0.34	2.00	50.80	0.11	0.16
00667506299	700		3/8	9.53	0.63	15.88	2	50	0.34	2.25	57.15	0.12	0.18
00667508299	700		1/2	12.70	0.78	19.83	2	35	0.24	3.00	76.20	0.16	0.24
00667503298	250		3/16	4.76	0.41	10.32	2	50	0.34	1.25	31.75	0.07	0.10
00667504298	250		1/4	6.35	0.50	12.70	2	50	0.34	1.50	38.10	0.09	0.13
00667505298	250		5/16	7.94	0.56	14.29	2	50	0.34	2.00	50.80	0.11	0.16
00667506298	250		3/8	9.53	0.63	15.88	2	50	0.34	2.25	57.15	0.12	0.18
25 ft. Coils													
00667503225	1 per carton		3/16	4.76	0.41	10.32	2	50	0.34	1.25	31.75	0.07	0.10
00667504225	1 per carton		1/4	6.35	0.50	12.70	2	50	0.34	1.50	38.10	0.09	0.13
00667505225	1 per carton		5/16	7.94	0.56	14.29	2	50	0.34	2.00	50.80	0.11	0.16
00667506225	1 per carton		3/8	9.53	0.63	15.88	2	50	0.34	2.25	57.15	0.12	0.18
50 ft. Coils													
00667503252	1 per carton		3/16	4.76	0.41	10.32	2	50	0.34	1.25	31.75	0.07	0.10
00667504252	1 per carton		1/4	6.35	0.50	12.70	2	50	0.34	1.50	38.10	0.09	0.13
00667505252	1 per carton		5/16	7.94	0.56	14.29	2	50	0.34	2.00	50.80	0.11	0.16
00667506252	1 per carton		3/8	9.53	0.63	15.88	2	50	0.34	2.25	57.15	0.12	0.18

AUTO/MARINE/COOLANT

**GEORGIA**  
3400 Town Point Dr.  
Suite 130  
Kennesaw, GA 30144

**OHIO**  
2611 Thunderhawk Ct.  
Dayton, OH 45414

**(800) 344-0150 phone**  
**(937) 454-2086 fax**  
**sales@ushoseco.com**  
**www.USHOSECO.com**