






HERCULES® II

A HIGH WORKING PRESSURE MULTIPURPOSE HOSE THAT IS A COST-EFFECTIVE ALTERNATIVE TO THE POPULAR HERCULES® 500. VALUE-ENGINEERED TO OFFER CUSTOMERS SUPERIOR PERFORMANCE IN HARSH WORK SITES LIKE FACTORIES, FOUNDRIES, MANUFACTURING PLANTS, MINES, QUARRIES AND NUMEROUS OTHER INDUSTRIAL APPLICATIONS.



<p>RESISTANCE</p> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;">  Abrasion </div> <div style="text-align: center;">  Fats/Oily Edibles </div> <div style="text-align: center;">  Gasoline </div> </div> <div style="display: flex; justify-content: space-around; margin-top: 10px;"> <div style="text-align: center;">  Kerosene </div> <div style="text-align: center;">  Oil </div> </div> <p>BRANDING: Thermoid Hercules II Multipurpose Hose Size I.D. 500 PSI WP MSHA 1C-209/7 Non-Conductive Made In USA</p> <p>COVER COLOR: Yellow</p>	<p>CONSTRUCTION: Non-Conductive</p> <ul style="list-style-type: none"> • Safety Assurance <p>TUBE: Nitrile, ARPM - Class A</p> <ul style="list-style-type: none"> • Capable of Handling Diesel, Kerosene and Gasoline • Capable of Handling Water <p>COVER: XNBR, ARPM - Class A</p> <ul style="list-style-type: none"> • Abrasion Resistant • Oil Resistant • Other Petroleum Products Resistant <p>REINFORCEMENT: 4-Spiral Yarn</p> <ul style="list-style-type: none"> • Provides a Working Pressure to 500 psi • More Flexible than Braid Reinforced Hose • Easier to Coil and Handle 	<p>TEMPERATURE RANGE: -40°F to +212°F, -40°C to +100°C</p> <p>PACKAGING: Reels</p> <ul style="list-style-type: none"> • 300-700 ft. Reels Depending on I.D. <p>MOLDED COVER PROCESS</p> <ul style="list-style-type: none"> • MSHA Approved Cover <p>MULTIPURPOSE HOSE</p> <ul style="list-style-type: none"> • Ideal for Extra Heavy Duty Use in Pneumatics or the Transfer of Liquids that Include Solvents, Oils or Other Petroleum Products <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Hercules II's yellow XNBR cover provides exceptional resistance to abrasion, oils and other petroleum-based products. Hercules II is the best value and a great selection for any OEM or MRO application requiring long life and exceptional performance in liquid transfer applications.</p> </div>
---	---	--

Product Number	Packaging	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
	Reels (ft.)	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
45454168662	500-700*	¼	6.35	0.63	15.88	4	500	3.45	1.50	38.10	0.14	0.21
45454248662	500-700*	⅜	9.53	0.75	19.05	4	500	3.45	2.25	57.15	0.21	0.31
45454328662	500-700*	½	12.70	0.91	23.02	4	500	3.45	3.00	76.20	0.24	0.36
45454488662	500-700*	¾	19.05	1.19	30.16	4	500	3.45	4.50	114.30	0.36	0.54
45454648662	300-450*	1	25.40	1.50	38.10	4	500	3.45	7.00	177.80	0.51	0.76
00454520500	550	1-¼	31.75	1.75	44.45	4	500	3.45	8.75	222.25	0.71	1.04
00454524500	400	1-½	38.10	2.09	53.09	4	500	3.45	10.50	266.70	1.00	1.49
00454532400	300	2	50.80	2.64	67.06	4	500	3.45	16.00	406.40	1.41	2.08

AIR - MULTIPURPOSE

GEORGIA
3400 Town Point Dr.
Suite 130
Kennesaw, GA 30144

OHIO
2611 Thunderhawk Ct.
Dayton, OH 45414

(800) 344-0150 phone
(937) 454-2086 fax
sales@ushoseco.com
www.USHOSECO.com