

# SERIES K6165 / K6158

## HIGH PURITY PVC POTABLE WATER HOSE

THE SERIES K6165 & K6158 ARE HIGH PURITY, NON-CONDUCTIVE, NSF-CERTIFIED, PHTHALATE-FREE PVC HOSES WITH A COLORED JACKET MAKING THIS PRODUCT IDEAL FOR POTABLE WATER AND DEIONIZED WATER TRANSFER.



### Construction:

- Tube – Clear Phthalate Free PVC compound, formulated in compliance with FDA<sup>(03)</sup> and NSF<sup>(12)</sup> criteria.
- Reinforcement – High tensile strength yarn.
- Cover – Phthalate Free PVC compound, available in two solid colors: K6155 – White and K6158 – Grey. Additional non-toxic colors (Red, Black, Blue, Green, Yellow and Purple) are available on a special order basis.

### Applications:

- Transfer of potable water.
- Transfer of deionized water.
- Induction welding tubing lines.
- Temporary residential water supply lines.
- Water transfer lines for semiconductor manufacturing, where applicable.
- Applications requiring a non-conductive hose.

### Service Temperature Range:

+25°F (-4°C) to +150°F (+65°C)

### Features:

- Made with Phthalate Free PVC compounds certified under NSF-51/NSF-61.
- White or gray jacket to reduce tendency for algae growth and U. V. degradation in warm sunny applications.
- Non-marking cover.
- Non-perforated cover.
- Non-conductive compounds.
- Silicone-free.
- One-piece lengths.
- RoHS<sup>(16)</sup> compliant.
- Now Phthalate Free!

## Nominal Specifications

Standard Stock Colors		Size Code	Nominal ID		Nominal OD		Maximum Working Pressure† (PSI)		Standard Length Coils	Approx. Wt. per Pkg.
K6155 White	K6158 Grey		(In)	(mm)	(In)	(mm)	@70°F (20°C)	@122°F (50°C)		
	✓	06	3/8	9.5	.594	15.1	225	125	300 ft.	27 lbs.
✓	✓	08	1/2	12.7	.750	19.1	200	100	300 ft.	40 lbs.
✓	✓	12	3/4	19.1	1.031	26.2	150	85	200 ft.	43 lbs.
✓	✓	16	1	25.4	1.300	33.0	125	75	200 ft.	59 lbs.
	✓	24	1 1/2	38.1	1.938	49.2	100	50	100 ft.	64 lbs.

FDA<sup>(03)</sup>, NSF<sup>(12)</sup>, PHTHALATE FREE<sup>(15)</sup>, RoHS<sup>(16)</sup>

**GEORGIA**  
3400 Town Point Dr.  
Suite 130  
Kennesaw, GA 30144

**OHIO**  
2611 Thunderhawk Ct.  
Dayton, OH 45414

(800) 344-0150 phone  
(937) 454-2086 fax  
sales@ushoseco.com  
www.USHOSECO.com