

# 300 PSI HOT TAR & ASPHALT APPLICATOR DELIVERY HOSE

THE T631AA SERIES IS DESIGNED SPECIFICALLY FOR HOT TAR AND ASPHALT DELIVERY SERVICE. RATED TO 300 PSI WORKING PRESSURE, ASSEMBLIES MADE WITH THIS PRODUCT ARE SUGGESTED TO BE USED WITH PERMANENTLY ATTACHED COUPLINGS



**Cover:**

Black CR – abrasion, ozone, hydrocarbon and fire resistant.

**Reinforcement:**

High tensile steel wire braids.

**Tube:**

Black NBR – hot tar and asphalt resistant.

**Safety Factor:**

10:1

**Working Pressure:**

20 Bar (300 PSI)

**Temperature Range:**

-22°F (-30°C) to 356°F (+180°C)

**Branding:**

ALFAGOMMA – ITALY T631 20 BAR (300 PSI) HOT TAR AND ASPHALT (embossed)

**Standard Length:**

100 feet

**Nominal Specifications**

Series	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Wall Thickness (mm)	Max Rec. WP (PSI)	Min. Bending Radius (in.)	Weight (lbs./ft.)
T631AA075	3/4	19	1.26	32	6	300	3	0.50
T631AA100	1	25	1.50	38	6	300	3	0.77

**GEORGIA**  
3400 Town Point Dr.  
Suite 130  
Kennesaw, GA 30144

**OHIO**  
2611 Thunderhawk Ct.  
Dayton, OH 45414

(800) 344-0150 phone  
(937) 454-2086 fax  
sales@ushoseco.com  
www.USHOSECO.com

SPECIALTY