

# 800 PSI PLASTER, GROUT & CONCRETE

THE 800 PSI WORKING PRESSURE T758 SERIES PLASTER, GROUT AND CONCRETE HOSE IS DESIGNED FOR PUMPING PLASTER, GROUT, AND WET CEMENT TO CONSTRUCTION PLACEMENT SITES AT RATED PRESSURES.



**Cover:**

Black SBR/NR.  
Blue SBR/EPDM.

**Reinforcement:**

Spiralled high tensile textile cords.

**Tube:**

Black conductive NR – abrasion-resistant.

**Working Pressure:**

Constant Pressure – 55 Bar (800 PSI)

**Temperature Range:**

-22°F (-30°C) to 176°F (+80°C)

**Branding:**

ALFAGOMMA – ITALY T758 – 55 BAR (800 PSI)  
PLASTER & CONCRETE (in white letters)

**COUPLING SUGGESTIONS**

Tubular steel full flow male permanently swaged or internally expanded with ferrule to provide maximum hose coupling compatibility.

**Nominal Specifications**

Series	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Max Rec. WP (PSI)	Weight (lbs./ft.)
T758AA/AE100	1	25	1.57	40	800	0.60
T758AA/AE125	1 1/4	32	1.93	49	800	0.85
T758AA/AE150	1 1/2	38	2.28	58	800	1.15
T758AA/AE200	2	51	2.80	71	800	1.49

MATERIAL HANDLING

**GEORGIA**  
3400 Town Point Dr.  
Suite 130  
Kennesaw, GA 30144

**OHIO**  
2611 Thunderhawk Ct.  
Dayton, OH 45414

(800) 344-0150 phone  
(937) 454-2086 fax  
sales@ushoseco.com  
www.USHOSECO.com