

# PLIOVIC® PLUS

A LIGHTWEIGHT, ECONOMICAL GENERAL PURPOSE HOSE FOR CARRYING AIR, WATER AND MANY SPRAY SOLUTIONS. PLIOVIC® IS SUITABLE FOR A WIDE RANGE OF INDUSTRIES, FROM CONSTRUCTION SITES TO AGRICULTURAL HAND SPRAYERS AND MANY MORE MULTIPURPOSE APPLICATIONS.



**CONSTRUCTION TUBE:** Black Pliovic®, RMA Class B (Medium Oil Resistance)

**COVER:** Pliovic®, smooth finish, RMA Class B (Medium Oil Resistance)

**REINFORCEMENT:** Spiral synthetic yarn

**TEMPERATURE:** -10 °F to 158 °F (-23 °C to 70 °C)

**COUPLINGS:** Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

**BRANDING:** Example: Pliovic® GS 3/8" ID (9.5 mm) 250 psi WP. Made in USA. Continental Contitech

Item #	I.D.	Nom. O.D.	Length	Color	Max. Working Pressure	Weight
<a href="#">20012588</a>	1/4 in 6.40 mm	0.500 in 12.70 mm	750.000 ft	Red	250.0 psi 1.72 MPa	0.080 lb/ft 0.12 kg/m
<a href="#">20012594</a>	3/8 in 9.50 mm	0.660 in 16.80 mm	750.000 ft	Red	250.0 psi 1.72 MPa	0.130 lb/ft 0.19 kg/m
<a href="#">20012605</a>	1/2 in 12.70 mm	0.810 in 20.60 mm	750.000 ft	Red	250.0 psi 1.72 MPa	0.170 lb/ft 0.25 kg/m
<a href="#">20012609</a>	5/8 in 15.90 mm	0.940 in 23.90 mm	500.000 ft	Red	250.0 psi 1.72 MPa	0.200 lb/ft 0.30 kg/m
<a href="#">20012610</a>	3/4 in 19.10 mm	1.110 in 28.20 mm	450.000 ft	Red	250.0 psi 1.72 MPa	0.280 lb/ft 0.42 kg/m
<a href="#">20012615</a>	1 in 25.40 mm	1.380 in 35.10 mm	400.000 ft	Red	200.0 psi 1.38 MPa	0.370 lb/ft 0.55 kg/m
<a href="#">20462276</a>	5/8 in 15.90 mm	0.940 in 23.90 mm	250.000 ft	Red	250.0 psi 1.72 MPa	0.200 lb/ft 0.30 kg/m

AIR - MULTIPURPOSE

**GEORGIA**  
3400 Town Point Dr.  
Suite 130  
Kennesaw, GA 30144

**OHIO**  
2611 Thunderhawk Ct.  
Dayton, OH 45414

**(800) 344-0150 phone**  
**(937) 454-2086 fax**  
**sales@ushoseco.com**  
**www.USHOSECO.com**

# PLIOVIC® PLUS

<u>Item #</u>	<u>I.D.</u>	<u>Nom. O.D.</u>	<u>Length</u>	<u>Color</u>	<u>Max. Working Pressure</u>	<u>Weight</u>
<a href="#">20012644</a>	1/4 in 6.40 mm	0.500 in 12.70 mm	750.000 ft	Blue	250.0 psi 1.72 MPa	0.080 lb/ft 0.12 kg/m
<a href="#">20012651</a>	3/8 in 9.50 mm	0.660 in 16.80 mm	750.000 ft	Blue	250.0 psi 1.72 MPa	0.130 lb/ft 0.19 kg/m
<a href="#">20012668</a>	1/2 in 12.70 mm	0.810 in 20.60 mm	750.000 ft	Blue	250.0 psi 1.72 MPa	0.170 lb/ft 0.25 kg/m
<a href="#">20012677</a>	5/8 in 15.90 mm	0.940 in 23.90 mm	500.000 ft	Blue	250.0 psi 1.72 MPa	0.200 lb/ft 0.30 kg/m
<a href="#">20012678</a>	3/4 in 19.10 mm	1.110 in 28.20 mm	450.000 ft	Blue	250.0 psi 1.72 MPa	0.280 lb/ft 0.42 kg/m
<a href="#">20012680</a>	1 in 25.40 mm	1.370 in 34.80 mm	400.000 ft	Blue	200.0 psi 1.38 MPa	0.370 lb/ft 0.55 kg/m
<a href="#">20462270</a>	5/8 in 15.90 mm	0.940 in 23.90 mm	250.000 ft	Blue	250.0 psi 1.72 MPa	0.200 lb/ft 0.30 kg/m
<a href="#">20012688</a>	1/4 in 6.40 mm	0.500 in 12.70 mm	750.000 ft	Green	250.0 psi 1.72 MPa	0.080 lb/ft 0.12 kg/m
<a href="#">20012691</a>	1/2 in 12.70 mm	0.810 in 20.60 mm	750.000 ft	Green	250.0 psi 1.72 MPa	0.170 lb/ft 0.25 kg/m
<a href="#">20012694</a>	3/4 in 19.10 mm	1.110 in 28.20 mm	450.000 ft	Green	250.0 psi 1.72 MPa	0.280 lb/ft 0.42 kg/m
<a href="#">20012696</a>	1/4 in 6.40 mm	0.500 in 12.70 mm	750.000 ft	Black	250.0 psi 1.72 MPa	0.080 lb/ft 0.12 kg/m
<a href="#">20012700</a>	3/8 in 9.50 mm	0.660 in 16.80 mm	750.000 ft	Black	250.0 psi 1.72 MPa	0.130 lb/ft 0.19 kg/m
<a href="#">20012703</a>	1/2 in 12.70 mm	0.810 in 20.60 mm	750.000 ft	Black	250.0 psi 1.72 MPa	0.170 lb/ft 0.25 kg/m
<a href="#">20012707</a>	1 in 25.40 mm	1.360 in 34.60 mm	400.000 ft	Black	250.0 psi 1.72 MPa	0.370 lb/ft 0.55 kg/m
<a href="#">20470083</a>	1 1/2 in 38.10 mm	1.980 in 50.20 mm	400.000 ft	Black	125.0 psi 0.86 MPa	0.720 lb/ft 1.07 kg/m
<a href="#">20012742</a>	1/4 in 6.40 mm	0.500 in 12.70 mm	750.000 ft	Yellow	250.0 psi 1.72 MPa	0.080 lb/ft 0.12 kg/m

AIR - MULTIPURPOSE

**GEORGIA**  
3400 Town Point Dr.  
Suite 130  
Kennesaw, GA 30144

**OHIO**  
2611 Thunderhawk Ct.  
Dayton, OH 45414

**(800) 344-0150 phone**  
**(937) 454-2086 fax**  
**sales@ushoseco.com**  
**www.USHOSECO.com**