

TYPE 65 BUTANE-PROPANE

THE TYPE 65 BUTANE-PROPANE HOSE IS DESIGNED TO TRANSFER LP GAS FROM BULK STORAGE TO TANK CARS OR CYLINDERS. IT IS LIGHTWEIGHT AND FLEXIBLE, AND FEATURES A BLACK CR COVER THAT IS OIL RESISTANT AND ALSO RESISTS SNAGGING, ABRASION AND WEATHER. ALL SIZES HAVE A FLEXIBLE STATIC WIRE AND THIS HOSE MEETS ALL UL REQUIREMENTS.



Cover Color:	Black
Oil Resistance:	High, Medium-High
Construction:	
Tube:	CR
Cover:	CR
Reinforcement:	High tensile cord
Temperature Range:	-40°F to +180°F -40°C to +82°C

Product Number	Nominal I.D.		Nominal O.D.		Plies**	Working Pressure		Min. Bend Radius		Weight	
	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
17814605*	1-1/4	31.75	1.81	46.04	4	350	2.41	8.00	203.20	0.92	1.37
17814610*	1-1/2	38.10	2.19	55.56	4	350	2.41	9.00	228.60	1.21	1.80
17814615*	2	50.80	2.75	69.85	4	350	2.41	12.00	304.80	1.77	2.63

* To order 50/100 ft., use product number and 002 = 100 ft. and 502 = 50 ft.

** Includes dual stainless steel static wire, spiral applied, in all sizes.

GEORGIA
3400 Town Point Dr.
Suite 130
Kennesaw, GA 30144

OHIO
2611 Thunderhawk Ct.
Dayton, OH 45414

(800) 344-0150 phone
(937) 454-2086 fax
sales@ushoseco.com
www.USHOSECO.com