


TYPE 75 BUTANE-PROPANE

THE TYPE 75 BUTANE-PROPANE HOSE WAS ENGINEERED FOR TRANSFERRING LIQUIFIED PROPANE GAS FROM BULK STORAGE TO TANK CARS OR CYLINDER, OR FROM BOBTAIL TRUCKS TO HOME STORAGE TANKS. THIS HOSE HAS BEEN PIN-PRICKED TO PERMIT GAS DIFFUSION, AND ITS SMOOTH BLACK COVER RESISTS OIL, SNAGGING, AND ABRASION.



| | | |
|---|---|--|
| <p>RESISTANCE</p>  <p>Abrasion Oil Weathering</p> <p>BRANDING: Thermoid Type 75 LPG Hose UL Listed Gas Hose Issue Number (Quarter) MH12585 350 PSI Maximum WP Made In USA</p> <p>COVER COLOR: Black</p> | <p>CONSTRUCTION</p> <p>TUBE: Nitrile, ARPM - Class A</p> <p>COVER: Type 75 - Chlorinated Polyethylene, ARPM - Class B: ¾" and 1" Type 75B - Nitrile Blend: ¼" - ½"</p> <ul style="list-style-type: none"> • Abrasion Resistant • Weather Resistant <p>REINFORCEMENT: 4- Spiral Yarn</p> <ul style="list-style-type: none"> • Provides a Working Pressure of 350 psi • More Flexible than Braid Reinforced Hose • Easier to Route Assemblies • Easier to Coil and Handle • Less Susceptible to Premature Failure than Braided Hose if Subjected to Torque | <p>TEMPERATURE RANGE: -40°F to +180°F, -40°C to +82°C</p> <p>PACKAGING: Reels, Coupled Lengths D.O.T. Test Certificate Included with Assemblies. Hose Assemblies Tested/Approved to 7/1/99 D.O.T. Regulations.</p> <p>UL 21 FILE MH 12585 OR UL 21 FILE MH 12585 LISTED/CSA APPROVED (CANADIAN STANDARDS APPROVAL)</p> <ul style="list-style-type: none"> • Meets All Industry Standards <p>PRO SUR FITTINGS AVAILABLE</p> <ul style="list-style-type: none"> • One-Piece Fitting Means No Leak Points |
|---|---|--|

| Product Number | Packaging | Nominal I.D. | | Nominal O.D. | | Reinforcement Spirals | Working Pressure | | Min. Bend Radius | | Weight | |
|-----------------|-------------|--------------|-------|--------------|-------|-----------------------|------------------|-------|------------------|--------|---------|--------|
| | Reels (ft.) | (inches) | (mm) | (inches) | (mm) | | (psi) | (Mpa) | (inches) | (mm) | (lb/ft) | (Kg/m) |
| TYPE 75B | | | | | | | | | | | | |
| 00667304600 | 700 | ¼ | 6.35 | 0.63 | 15.88 | 4 | 350 | 2.41 | 1.50 | 38.10 | 0.14 | 0.22 |
| 00667306600 | 700 | ⅜ | 9.53 | 0.75 | 19.05 | 4 | 350 | 2.41 | 2.25 | 57.15 | 0.18 | 0.30 |
| 00667308600 | 700 | ½ | 12.70 | 0.94 | 23.81 | 4 | 350 | 2.41 | 3.00 | 76.20 | 0.29 | 0.43 |
| TYPE 75 | | | | | | | | | | | | |
| 22074481662 | 500-700* | ¾ | 19.05 | 1.25 | 31.75 | 4 | 350 | 2.41 | 4.50 | 114.30 | 0.27 | 0.61 |
| 22074641662 | 300-500* | 1 | 25.40 | 1.50 | 38.10 | 4 | 350 | 2.41 | 7.00 | 177.80 | 0.58 | 0.86 |

GEORGIA
3400 Town Point Dr.
Suite 130
Kennesaw, GA 30144

OHIO
2611 Thunderhawk Ct.
Dayton, OH 45414

(800) 344-0150 phone
(937) 454-2086 fax
sales@ushoseco.com
www.USHOSECO.com