

TIGERFLEX® W™ SERIES

HEAVY DUTY PVC LIQUID SUCTION HOSE

General Applications:

- Extreme cold conditions (Sizes 4" - 16")
- Fish suction
- Gold dredging
- Pumps, rental and construction dewatering
- Pumps, trash
- Slurry handling
- Water suction – heavy duty

Construction: PVC tube with rigid PVC helix.

Service Temperature Range:

Sizes 1" - 3": -4°F (-20°C) to +150°F (+65°C)*;
 Sizes 4" - 16": -40°F (-40°C) to +150°F (+65°C)*



Features and Advantages:

- **“Cold-Flex” Materials (Sizes 4" - 16")** – Hose remains flexible in sub-zero temperatures.
- **Transparent Construction** – “See-the-flow.” Allows for visual confirmation of material flow.
- **Convoluting Outer Cover** – Provides increased hose flexibility.
- **Phthalate Free**

Nominal Specifications

Series Number	ID		OD		Working Pressure (psi)		Vacuum Rating Hg (in)		Min. Bending Radius at 68°F (in)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	68°F	104°F	68°F	104°F			
W100	1	25.4	1.30	33.0	55	35	Full	28	1	100	0.21
W125	1-1/4	31.7	1.60	40.6	50	30	Full	28	2	100	0.28
W150	1-1/2	38.1	1.85	47.0	50	30	Full	28	2	100	0.34
W200	2	50.8	2.40	61.0	50	30	Full	28	3	100	0.52
W250	2-1/2	63.5	2.99	75.9	45	25	Full	28	4	100	0.77
W300	3	76.2	3.64	92.5	45	25	Full	28	6	100	1.18
W400	4	101.6	4.76	121.0	35	18	Full	28	8	100	1.92
W500	5	127.0	5.75	146.0	35	18	28	25	12	100/20	2.95
W600	6	152.4	7.00	177.8	30	15	28	25	14	100/20	3.76
W800	8	203.2	9.18	233.2	30	15	28	25	24	40/20	5.99
W1000	10	254.0	11.56	293.5	25	12	28	25	39	40/20	9.74
W1200	12	304.8	13.64	346.5	20	10	28	25	59	40/20	12.77
W1400†	14	357.6	15.59	396.0	18	8	26	23	80	20	13.50
W1600†	16	408.4	17.72	450.0	12	5	24	20	95	20	16.00

GEORGIA
 3400 Town Point Dr.
 Suite 130
 Kennesaw, GA 30144

OHIO
 2611 Thunderhawk Ct.
 Dayton, OH 45414

(800) 344-0150 phone
(937) 454-2086 fax
 sales@ushoseco.com
 www.USHOSECO.com

PVC