

# 225 PSI PREMIUM WASH DOWN PAPER MILL / CREAMERY HOSE - NO NOZZLE

THE T350 SERIES IS SPECIALLY DESIGNED FOR GENERAL WASH DOWN SERVICE, USING HOT WATER OR LOW PRESSURE SATURATED STEAM IN PROCESSING PLANTS AND FACILITIES AND IN FOOD AND DIARY PLANTS.



**Cover:**

Red EPDM – heat, abrasion and ozone resistant.  
White EPDM – heat, abrasion and ozone resistant.

**Reinforcement:**

High tensile textile cords.

**Tube:**

White EPDM.

**Working Pressure:**

Constant Pressure – 15 Bar (225 PSI)

**Steam Pressure:**

Constant Pressure – 6 Bar (90 PSI)

**Temperature Range:**

-40°F (-40°C) to 330°F (+165°C)

**Branding:**

ALFAGOMMA – ITALY – T350 6 BAR (90 PSI) STEAM  
15 BAR (225 PSI) HOT WATER (embossed)

**Nominal Specifications**

Series	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Max Rec. WP (PSI)	Weight (lbs./ft.)
T350LL050	1/2	13	0.91	23	225	0.27
T350LL062	5/8	16	1.02	26	225	0.31
T350LL075	3/4	19	1.22	31	225	0.44
T350LL100	1	25	1.46	37	225	0.54
T350LH075	3/4	19	1.22	31	225	0.44
T350LH100	1	25	1.46	37	225	0.54

**COUPLING SUGGESTIONS**

Short shank, long shank couplings (NPT, GHT), barbed inserts attached with bands.

**GEORGIA**  
3400 Town Point Dr.  
Suite 130  
Kennesaw, GA 30144

**OHIO**  
2611 Thunderhawk Ct.  
Dayton, OH 45414

(800) 344-0150 phone  
(937) 454-2086 fax  
sales@ushoseco.com  
www.USHOSECO.com

**FOOD & BEVERAGE**