

150 PSI PREMIUM WASH DOWN PAPER MILL / CREAMERY HOSE WITH TAPERED NOZZLE

THE SERIES T351 HOSE IS DESIGNED SPECIFICALLY FOR GENERAL WASH DOWN SERVICE, USING HOT AND COLD WATER IN PAPER MILLS AND IN FOOD AND DAIRY PLANTS.



Cover:

White or green EPDM – heat, abrasion and ozone resistant.

Reinforcement:

High tensile textile cords.

Tube:

White EPDM.

Working Pressure:

Constant Pressure – 10 Bar (150 PSI)

Temperature Range:

-40°F (-40°C) to 248°F (+120°C)

***Tapered Nozzle Hole Size**

3/4" and 1" ID 3/8"
1 1/4" ID..... 1/2"
1 1/2" ID..... 5/8"

| Nominal Specifications | | | | | | |
|------------------------|----------|---------|----------|---------|-------------------|-------------------|
| Series | ID (in.) | ID (mm) | OD (in.) | OD (mm) | Max Rec. WP (PSI) | Weight (lbs./ft.) |
| T351LL/LG075 | 3/4 | 19 | 1.22 | 31 | 150 | 0.44 |
| T351LL/LG100 | 1 | 25 | 1.46 | 37 | 150 | 0.54 |
| T351LL/LG125 | 1 1/4 | 32 | 1.81 | 46 | 150 | 0.78 |
| T351LL/LG150 | 1 1/2 | 38 | 2.05 | 52 | 150 | 0.91 |

COUPLING SUGGESTIONS

Short shank, long shank couplings (NPT, GHT), barbed inserts attached with bands.

FOOD & BEVERAGE

GEORGIA
3400 Town Point Dr.
Suite 130
Kennesaw, GA 30144

OHIO
2611 Thunderhawk Ct.
Dayton, OH 45414

(800) 344-0150 phone
(937) 454-2086 fax
sales@ushoseco.com
www.USHOSECO.com