

# SILCO SLEEVE® FIRESLEEVE

SILCO SLEEVE® FIRESLEEVE IS DESIGNED TO PROTECT HOSES, WIRES AND CABLES FROM THE HAZARDS OF HIGH HEAT AND OCCASIONAL FLAME. IT PROTECTS CONTINUOUSLY TO 550°F (260°C) AND WILL WITHSTAND A MOLTEN SPLASH AT 2200°F (1200°C). MADE OF KNITTED FIBERGLASS YARNS IN A FLEXIBLE SUBSTRATE, THIS PRODUCT IS THEN COATED WITH A HIGH GRADE SILICONE RUBBER.



PART NO.	HOSE I.D.	SLEEVE SIZE	WEIGHT (LBS/FT)
S-E13610-08-RO	3/8"	1/2"	0.12
S-E13610-12-RO	1/2"	3/4"	0.17
S-E13610-24-RO	1"	1-1/2"	0.31
S-E13610-32-RO	1-1/2"	2"	0.43
S-E13610-48-RO	2"	3"	0.60

CERTIFICATIONS / APPROVALS / STANDARDS	INDUSTRIAL
ASTM D-578	✓
UL 94 Flammability V1 Certified	✓
UL 1441 Flammability VW1 Certified	✓
UL 1581 Vertical Wire Testing Certified	✓
REACH Compliant	✓
RoHS Compliant	✓
Conflict Material Free	✓
Asbestos Free	✓
Does not contain chemicals listed under on California's Safe Drinking Water & Toxic Enforcement Act of 1986. Commonly known as Proposition 65 (Cal Prop 65).	✓

Resistant to hydraulic fluids, lubricating oils, and fuels, Silco Sleeve insulates against energy loss in piping and hosing, protects employees from burns and allows "bundling" of wires, hoses, and cables. The braided version meets the performance requirements of various industry standards.

#### MATERIALS

Type E Fiberglass  
Silicone Elastomer Coating

#### AVAILABLE CONSTRUCTION OPTIONS

Knitted (Industrial)

#### MAXIMUM CONTINUOUS TEMPERATURE

500°F (260°C)

#### SIZE RANGE

3/8" (9.6mm) - 2" (51mm)

#### TYPICAL INDUSTRIES

Hose Fabrication, Oil & Gas, OEM, Metals, Locomotive

**GEORGIA**  
3400 Town Point Dr.  
Suite 130  
Kennesaw, GA 30144

**OHIO**  
2611 Thunderhawk Ct.  
Dayton, OH 45414

**(800) 344-0150 phone**  
**(937) 454-2086 fax**  
**sales@ushoseco.com**  
**www.USHOSECO.com**

**FIRESLEEVE**