

EXTRA FLEXIBLE NITRILE FOOD

150 PSI SUCTION & DISCHARGE HOSE

RECOMMENDED FOR OILY & NON-OILY FOOD & BEVERAGE TRANSFER APPLICATIONS THAT DEMAND BOTH FLEXIBILITY AND RUGGEDNESS. THE FOOD GRADE NITRILE TUBE IS ODORLESS AND TASTELESS FOR THOSE OILY TRANSFER APPLICATIONS. THIS ULTRA SMOOTH MICROBE RESISTANT TUBE IS BUILT OF SPECIAL STAINLESS STEEL MANDRELS FOR CLEANLINESS.



Construction:

Tube: FDA white nitrile

Reinforcement: Multiple plies of polyester tire cord with helix wire

Cover: Grey PVC nitrile corrugated

Length: 100 ft.

Temperature Range -40°F (-40°C) to +210°F (+99°C)

Cleaning in Place to 248°F (+120°C)

Not for continuous steam service

NOTE: Meets FDA, USDA & 3A sanitary standards Authorized #1376.

Part No.	I.D.	O.D.	Plies	WP psi	MBR	WT LBS/FT
6314WT-01500-00	1½	2.05	2	150	2"	1.04
6314WT-02000-00	2	2.55	2	150	3"	1.34
6314WT-02500-00	2½	3.05	2	150	4"	10.57
6314WT-03000-00	3	3.75	2	150	5"	2.78
6314WT-04000-00	4	4.76	2	150	6.5"	3.82

GEORGIA
3400 Town Point Dr.
Suite 130
Kennesaw, GA 30144

OHIO
2611 Thunderhawk Ct.
Dayton, OH 45414

(800) 344-0150 phone
(937) 454-2086 fax
sales@ushoseco.com
www.USHOSECO.com

FOOD & BEVERAGE