




GREEN NON-MARKING PUMPFLEX® MARINE FUEL HOSE

DESIGNED TO HANDLE AND PERFORM IN SEVERE WEATHER CONDITIONS, THIS DURABLE SOFTWALL GAS HOSE IS IDEAL FOR ROUGH DECK OR DOCK USE. THE OIL AND WEATHER RESISTANT UL-APPROVED COVER IS GREEN COLOR-CODED TO DESIGNATE MARINA USE. **NOTE: CAN BE USED FOR ALL TYPES OF GASOLINE, OIL AND OTHER PETROLEUM PRODUCTS.**



RESISTANCE    Gasoline Oil Weathering			CONSTRUCTION TUBE: Nitrile Blend, ARPM - Class A <ul style="list-style-type: none"> • High Oil Resistant • Handles Gasoline • Handles Oil • Handles Other Petroleum Products COVER: Chlorinated Polyethylene, ARPM - Class A <ul style="list-style-type: none"> • Medium-High Oil Resistant • Weather Resistant REINFORCEMENT: 4-Spiral Polyester Yarn with Static Wire (Softwall) <ul style="list-style-type: none"> • Provides a Working Pressure to 150 to 200 psi 				TEMPERATURE RANGE: -40°F to +180°F, -40°C to +82°C PACKAGING: Reels <ul style="list-style-type: none"> • Color Codes this Hose for Marina Use STATIC WIRE, ALL SIZES <ul style="list-style-type: none"> • Enables User to Ground the Hose, Dissipating a Build Up of Electricity 					
Product Number	Packaging	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
	Reels (ft.)	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
22463484662	500	¾	19.05	1.13	28.58	4	200	1.38	4.50	114.30	0.32	0.48
22464644662	500	1	25.40	1.50	38.10	4	150	1.03	7.00	177.80	0.62	0.92

AUTO/MARINE/COOLANT

GEORGIA
3400 Town Point Dr.
Suite 130
Kennesaw, GA 30144

OHIO
2611 Thunderhawk Ct.
Dayton, OH 45414

(800) 344-0150 phone
(937) 454-2086 fax
sales@ushoseco.com
www.USHOSECO.com