

3859 HOT TAR & ASPHALT HOSE

DESIGNED FOR THE
TRANSFER OF TAR,
ASPHALT, HOT OILS AND
OTHER HIGH
TEMPERATURE
PETROLEUM-BASED
PRODUCTS.

**NOT FOR USE WITH
BIOFUELS**



Construction:

Tube: Black high grade nitrile rubber
Reinforcement: Plies of polyester tire cord with helix wire
Cover: Smooth black abrasion resistant nitrile
Length: 100 ft.
Temperature Range: -40° (-40°C) to +350°F (+177°C)
(Intermittent service only)

Not for use with BioFuels

When coupling chemical and higher risk hoses, Novaflex® recommends the use of crimp couplings using interlocking crimp ferrules.

| Part No. | I.D. | O.D. | Plies | MBR (in) | WP psi | VAC HG | WT LBS/FT |
|-----------------|------|------|-------|----------|--------|--------|-----------|
| 3859BT-02000-00 | 2 | 2.72 | 2 | 6 | 150 | 30" | 1.18 |
| 3859BT-02500-00 | 2½ | 3.24 | 2 | 7 | 150 | 30" | 1.56 |
| 3859BT-03000-00 | 3 | 3.79 | 2 | 9 | 150 | 30" | 1.84 |
| 3859BT-04000-00 | 4 | 4.79 | 2 | 12 | 150 | 30" | 2.39 |

SPECIALTY