

ALFAJET 210 PRESSURE WASHER HOSE

THE ALFAJET 210 IS A SINGLE WIRE BRAID, HIGH PRESSURE CLEANING HOSE FOR HEAVY DUTY USE WITH HOT AND COLD WATER AND DETERGENT FLUIDS, AND HIGH PRESSURE CLEANING EQUIPMENT. EXTREMELY FLEXIBLE, LIGHT WEIGHT AND EASY TO HANDLE. ***NOT RECOMMENDED FOR STEAM SERVICE.**



Construction:

Tube – Synthetic rubber, black... hot water-resistant.

Reinforcement – High tensile steel wire braid.

Cover – Synthetic rubber, black or blue, non-marking... weather, oil, ozone and abrasion-resistant.

Branding – ALFAGOMMA ALFAJET 210 ID ...DN ... 210 Bar WP - 155°C

Use bend restrictors to extend service life.

Special identification with embossed layline.

BK = Black Cover

BU = Blue Cover

Temperature Range: -40°F (-40°C) to 300°F (155°C) constant operation.

Maximum operating temperature: 300°F (155°C). **Air maximum temperature:** 175°F (80°C).

Note: Operating temperatures in excess of 300°F (155°C) may materially reduce the life of the hose.

Nominal Specifications

Series Number	Size Code	Nominal ID		Nominal OD		Max Working [†] Pressure (psi)	Min. Bend. Radius		Approx. Weight (lbs./ft.)	Coupling Recommendations	
		(in.)	(mm)	(in.)	(mm)		(in.)	(mm)		AlfaCrimp One-Piece	Two-Piece Couplings Ferrule Non-Skive
TAJ3BK	04	1/4	6.4	0.48	12.1	3,000	2.0	50	0.11	B	AF1
TAJ3BK	05	5/16	7.9	0.56	14.1	3,000	2.4	60	0.13	B	AF1
TAJ3BK	06	3/8	9.5	0.61	15.6	3,000	2.6	65	0.17	B	AF1
TAJ3BK	08	1/2	12.7	0.77	19.5	3,000	3.6	90	0.27	B	AF1
TAJ3BU	04	1/4	6.4	0.48	12.1	3,000	2.0	50	0.11	B	AF1
TAJ3BU	05	5/16	7.9	0.56	14.1	3,000	2.4	60	0.13	B	AF1
TAJ3BU	06	3/8	9.5	0.61	15.6	3,000	2.6	65	0.17	B	AF1
TAJ3BU	08	1/2	12.7	0.77	19.5	3,000	3.6	90	0.27	B	AF1

[†] Minimum burst pressure 4-to-1 safety factor.

STANDARD PRESSURE