

FLEXSTEEL® 250 STEAM HOSE

FLEXSTEEL® 250 IS DESIGNED FOR CLEANING, HEAT CONTROL, FIRE PREVENTION, PUMPING, THAWING, BLOW-OUT SERVICE, STEAM PUMPS AND HOISTS IN OPEN-END OR PERMANENT INSTALLATION OPERATIONS. THIS PRODUCT IS USED IN REFINERIES, SHIPYARDS, CHEMICAL PLANTS, STEEL MILLS, FOUNDRIES AND HEAVY INDUSTRIAL APPLICATIONS WHERE HIGH STRENGTH IS REQUIRED AND WHERE SEVERE ENVIRONMENTAL CONDITIONS ARE ENCOUNTERED.



CONSTRUCTION TUBE: Pyrosyn® synthetic rubber

COVER: Black or Red Pyrosyn, smooth finish, pin-pricked

REINFORCEMENT: Braided steel wire (3/4" and 1" have 2 steel wire braids)

TEMPERATURE: 0 °F to 450 °F (-18 °C to 232 °C)

COUPLINGS: See Continental Contitech Hose Assembly Manual for most current crimp solutions. 1/2 in ID is not for use with crimped fittings. 1 in ID Red is not for use with crimped fittings.

BRANDING: Example: Continental Contitech Flexsteel® 250 Steam (DC) Drain after using. Made in USA.

| <u>Item #</u> | <u>I.D.</u> | <u>Nom. O.D.</u> | <u>Color</u> | <u>Weight</u> |
|---------------|--------------------|----------------------|--------------|--------------------------|
| 2002-3390 | 1/2 in 12.70 mm | 1.060 in 26.90 mm | Black | 0.420 lb/ft 0.63 kg/m |
| 2002-3404 | 3/4 in 19.10 mm | 1.280 in 32.50 mm | Black | 0.550 lb/ft 0.82 kg/m |
| 2002-3419 | 1 in 25.40 mm | 1.630 in 41.40 mm | Black | 0.910 lb/ft 1.35 kg/m |