

CONNOISSEURS 6506

KINK AND CRUSH RESISTANT SUCTION & DISCHARGE HOSE, DESIGNED FOR THOSE MORE DEMANDING APPLICATIONS REQUIRING A PRODUCT THAT MEETS 3-A, FDA, AND USDA STANDARDS. DESIGNED TO MEET THE TEMPERATURES AND CHEMICAL RESISTANCE ASSOCIATED WITH CIP/SIP SYSTEMS. THIS ULTRA SMOOTH MICROBE RESISTANT TUBE IS BUILT FOR NON-OILY APPLICATIONS.



Construction:

Tube: White Chlorobutyl (non oily applications)

Reinforcement: Multiple plies of polyester tire cord & dual monofilament helix

Cover: Gray EPDM abrasion resistant. Length: 100 ft

Temperature Range: -40°F (-40°C) to +240°F (+116°C)

(Cleaning In Place to 248°F (+120°C) Not for continuous steam service

Part No.	I.D.	O.D.	MBR (in)	VAC (Hg)	Plies	WP psi	WT LBS/FT
6506WB-00750-00	¾	1.41	3.0	Full	2	250	0.33
6506WB-01000-00	1	1.64	3.5	Full	2	250	0.44
6506WB-01500-00	1½	2.14	4.5	Full	2	250	0.63
6506WB-02000-00	2	2.77	7.0	Full	4	250	1.21
6506WB-02500-00	2½	3.29	13.0	Full	4	250	1.52
6506WB-03000-00	3	3.79	16.0	Full	4	250	1.84

FOOD & BEVERAGE