

# GORILLA®

A PREMIUM-QUALITY, MULTIPURPOSE INDUSTRIAL HOSE WITH A WIDE RANGE OF APPLICATIONS IN FACTORIES, CONSTRUCTION, AGRICULTURE, QUARRIES, MINES, RAILROADS, THE OIL & GAS INDUSTRY AND SHIPBUILDING. ALL SIZES RATED AT 500 PSI MAX W.P. NON-CONDUCTIVE WITH A MINIMUM ELECTRICAL RESISTANCE GREATER THAN 1 MEGOHM PER INCH OF HOSE LENGTH AT 1000 VOLTS DC.



**Tube:** Nitrile synthetic rubber, RMA Class A (High Oil Resistance)

**Cover:** Yellow Carbryn® synthetic rubber, RMA Class A (High Oil Resistance) MSHA approved

**Reinforcement:** Spiral aramid yarn, 2" is braided synthetic yarn

**Temperature Range:** -20°F to 210°F (-29°C to 99°C)

**Branding:** Gorilla® 1" (25.4 mm) 500 psi. Made in U.S.A. Continental ContiTech. Flame Resistant USMSHA No. 2G-14C/14.

ID		Nom. OD		Max. WP		Weight	
in.	mm	in.	mm	psi	MPa	lbs./ft.	kg/m
1/4	6.4	0.61	15.5	500	3.45	0.17	0.25
3/8	9.5	0.73	18.6	500	3.45	0.22	0.33
1/2	12.7	0.89	22.6	500	3.45	0.28	0.42
3/4	19.1	1.19	30.2	500	3.45	0.41	0.61
1	25.4	1.5	37.8	500	3.45	0.58	0.86
1-1/4	31.8	1.77	45.6	500	3.45	0.79	1.18
1-1/2	38.1	2.04	51.8	500	3.45	0.86	1.27
2	50.8	2.62	66.6	500	3.45	1.22	1.82

\*Not for use with ultra-low sulfur diesel in potentially high-flex reeling applications.

AIR - MULTIPURPOSE