





# GREEN GP / OXYGEN

THE GREEN GP/OXYGEN HOSE IS DESIGNED TO HANDLE THE HARSH, ABUSIVE CONDITIONS FOUND IN STEEL PRODUCING AND OIL REFINERY ENVIRONMENTS. THE GREEN COVER FOLLOWS THE COLOR CODING FOR OXYGEN IN MILLS.



**\*NOT RECOMMENDED FOR FUEL OR AIR BREATHING APPLICATIONS.**

<p><b>RESISTANCE</b></p> <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;">  Abrasion         </div> <div style="text-align: center;">  Oil         </div> <div style="text-align: center;">  Ozone         </div> <div style="text-align: center;">  Weathering         </div> </div> <p><b>BRANDING:</b> Size 300# W.P. -GP/OXYGEN MADE IN USA Date and Time Stamp</p> <p><b>COVER COLOR:</b> Green • Allows for Color Coding</p>	<p><b>CONSTRUCTION</b></p> <p><b>TUBE:</b> Nitrile Blend, ARPM - Class B</p> <p><b>COVER:</b> Nitrile Blend, ARPM - Class B</p> <ul style="list-style-type: none"> <li>• Abrasion Resistant</li> <li>• Weather Resistant</li> <li>• Ozone Resistant</li> </ul> <p><b>REINFORCEMENT:</b> 4-Spiral Polyester Yarn</p> <ul style="list-style-type: none"> <li>• Provides a Working Pressure to 300 psi</li> <li>• More Flexible than Braid Reinforced Hose</li> <li>• Easier to Route Assemblies</li> <li>• Easier to Coil and Handle</li> <li>• Less Susceptible to Premature Failure than Braided Hose if Subjected to Torque</li> </ul>	<p><b>TEMPERATURE RANGE:</b> -20°F to +180°F, -29°C to +82°C</p> <p><b>PACKAGING:</b> Reels</p> <ul style="list-style-type: none"> <li>• 700 ft. Reels</li> <li>• Over 80% One Piece Reels</li> <li>• Less Scrap</li> <li>• Most Footage per Reel vs. Competition</li> </ul> <p><b>PRESSURELESS CURE SYSTEM</b></p> <ul style="list-style-type: none"> <li>• Minimal Cast (Natural Curvature of the Hose)</li> <li>• Extends the Life of the Rubber Compounds</li> </ul> <p><b>AIR MANDREL MANUFACTURING PROCESS</b></p> <ul style="list-style-type: none"> <li>• No Internal Contamination of the Inside Diameter Due to the Lubricant</li> <li>• Eliminates the Need for Customers to Flush the Hose</li> </ul>
--	---	---

Product Number	Packaging	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius	
	Reels (ft.)	inches	mm	inches	mm		psi	Mpa	inches	mm
00336606400	700	3/8	9.53	0.71	22.23	4	300	2.07	2.25	57.15
00336608400	700	1/2	12.70	0.94	23.81	4	300	2.07	3.00	76.20
00336612400	700	3/4	19.05	1.16	29.37	4	300	2.07	4.50	114.30

**AIR - MULTIPURPOSE**