

# 75 PSI HEAVY WEIGHT DRY POWDER DELIVERY HOSE

THIS HOSE IS IDEAL FOR DISCHARGE OF DRY POWDERS UNDER LOW PRESSURE AND PNEUMATIC TRANSFER OF DRY MATERIALS AND ABRASIVE SLURRIES.



**Cover:**

Black conductive SBR/NR blend – abrasion and ozone resistant.

**Reinforcement:**

Spiralled high tensile textile cords.

**Tube:**

1/4" black static conducting NR – compounded to resist cutting by abrasive materials.

**Working Pressure:**

Constant Pressure – 5 Bar (75 PSI)

**Temperature Range:**

-22°F (-30°C) to 176°F (+80°C)

**Branding:**

ALFAGOMMA – ITALY T763 5 BAR (75 PSI) BULK MATERIAL DELIVERY (in green letters)

**COUPLING SUGGESTIONS**

Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.

Series	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Max Rec. WP (PSI)	Weight (lbs./ft.)
T763AA400	4	102	4.72	120	75	2.14
T763AA450	4 1/2	115	5.24	133	75	2.30
T763AA500	5	127	5.71	145	75	2.60

★ Excessive bending during operation may cause premature wear.

MATERIAL HANDLING