



## $PATRIOT^{e}1776C$ EXTREME CHEMICAL

LIGHTWEIGHT AND FLEXIBLE, THE PATRIOT® EXTREME CHEMICAL **SUCTION & DISCHARGE** HOSE IS DESIGNED TO HANDLE MOST EVERY



### **COMMON INDUSTRIAL** CHEMICAL IN USE TODAY.

# 1776C

**TUBE:** Clear ultra high molecular weight polyethylene **COVER:** Blue abrasion resistant EPDM **REINFORCEMENT:** Multiple plies of high tensile textile with dual helix.

SERVICE TEMPERATURE RANGE: -40°F To +250°F (-40°C To +121°C)

**NOT FOR STEAM SERVICE:** Open end steam cleaning is allowed.

#### **FEATURES:**

- Food grade quality meets FDA & USDA standards
- Non-staining UHMWPE tube
- Corrugated cover (C-Series) offering greater flexibility

NOMINAL SPECIFICATIONS													
PART NO.		I.D. (mm)			PLIES	VACUUM (Hg)	MBR (in)		WEIGHT (lbs/ft)				

1776C-100-USH 1	25.4	1.50 38.10	2	29"	3	250	0.63
1776C-150-USH 1.5	38.1	2.10 53.34	2	29"	4	250	1.06
1776C-200-USH 2	50.8	2.61 66.29	2	29"	6	250	1.33
1776C-300-USH 3	76.2	3.66 92.96	2	29"	12	200	2.12

#### WARNING! NEVER USE PATRIOT® 1776 OR 1776C ABOVE US HOSE & COUPLING'S RATINGS

The chemical resistance rating can change with temperature rise. Please verify that the chemical to be transferred is safely rated for use with this hose by checking our chemical resistance chart. Because chemicals become more aggressive at elevated temperatures, the UHMWPE tube may experience a reduction in resistance. Therefore verify the chemical temperature and concentration with our ratings. No data assumes responsibility lies with the end user.

(800) 344-0150 phone sales@ushoseco.com 2611 Thunderhawk Ct. **Dayton, OH 45414** (937) 454-2086 fax www.USHOSECO.com