

800 PSI PLASTER, GROUT & CONCRETE

THE 800 PSI WORKING PRESSURE T758 SERIES PLASTER, GROUT AND CONCRETE HOSE IS DESIGNED FOR PUMPING PLASTER, GROUT, AND WET CEMENT TO CONSTRUCTION PLACEMENT SITES AT RATED PRESSURES.



Cover:

Black SBR/NR.
Blue SBR/EPDM.

Reinforcement:

Spiralled high tensile textile cords.

Tube:

Black conductive NR – abrasion-resistant.

Working Pressure:

Constant Pressure – 55 Bar (800 PSI)

Temperature Range:

-22°F (-30°C) to 176°F (+80°C)

Branding:

ALFAGOMMA – ITALY T758 – 55 BAR (800 PSI)
PLASTER & CONCRETE (in white letters)

COUPLING SUGGESTIONS

Tubular steel full flow male permanently swaged or internally expanded with ferrule to provide maximum hose coupling compatibility.

Nominal Specifications

Series	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Max Rec. WP (PSI)	Weight (lbs./ft.)
T758AA/AE100	1	25	1.57	40	800	0.60
T758AA/AE125	1 1/4	32	1.93	49	800	0.85
T758AA/AE150	1 1/2	38	2.28	58	800	1.15
T758AA/AE200	2	51	2.80	71	800	1.49

MATERIAL HANDLING