

600 PSI PLASTER & CONCRETE

THE 600 PSI WORKING PRESSURE T757AA & T737AA SERIES PLASTER AND CONCRETE HOSE IS DESIGNED FOR PUMPING PLASTER, GROUT, AND WET CEMENT TO PLACEMENT SITES.



Cover:

Black conductive SBR/NR – abrasion and ozone resistant.

Reinforcement:

High tensile textile cords.

Tube:

Black conductive NR – abrasion resistant.

Working Pressure:

Constant Pressure – 40 Bar (600 PSI)

Temperature Range:

-22°F (-30°C) to 176°F (+80°C)

Branding:

ALFAGOMMA – ITALY T757 – 40 BAR (600 PSI) PLASTER & CONCRETE (in white letters) and ALFAGOMMA – ITALY T737 – 40 BAR (600 PSI) PLASTER & CONCRETE (in white letters)

COUPLING SUGGESTIONS

Tubular steel full flow male permanently swaged or internally expanded with ferrule to provide maximum hose coupling compatibility.

Nominal Specifications						
Series	ID (in.)	ID (mm)	OD (in.)	OD (mm)	Max Rec. WP (PSI)	Weight (lbs./ft.)
T757AA150	1 1/2	38	2.13	54	600	0.82
T757AA200	2	51	2.64	67	600	1.09
T737AA300	3	76	4.09	104	600	2.96

MATERIAL HANDLING