


TYPE 75 BUTANE-PROPANE

THE TYPE 75 BUTANE-PROPANE HOSE WAS ENGINEERED FOR TRANSFERRING LIQUIFIED PROPANE GAS FROM BULK STORAGE TO TANK CARS OR CYLINDER, OR FROM BOBTAIL TRUCKS TO HOME STORAGE TANKS. THIS HOSE HAS BEEN PIN-PRICKED TO PERMIT GAS DIFFUSION, AND ITS SMOOTH BLACK COVER RESISTS OIL, SNAGGING, AND ABRASION.



<p>RESISTANCE</p>  <p>Abrasion Oil Weathering</p> <p>BRANDING: Thermoid Type 75 LPG Hose UL Listed Gas Hose Issue Number (Quarter) MH12585 350 PSI Maximum WP Made In USA</p> <p>COVER COLOR: Black</p>	<p>CONSTRUCTION</p> <p>TUBE: Nitrile, ARPM - Class A</p> <p>COVER: Type 75 - Chlorinated Polyethylene, ARPM - Class B: ¾" and 1" Type 75B - Nitrile Blend: ¼" - ½"</p> <ul style="list-style-type: none"> • Abrasion Resistant • Weather Resistant <p>REINFORCEMENT: 4- Spiral Yarn</p> <ul style="list-style-type: none"> • Provides a Working Pressure of 350 psi • More Flexible than Braid Reinforced Hose • Easier to Route Assemblies • Easier to Coil and Handle • Less Susceptible to Premature Failure than Braided Hose if Subjected to Torque 	<p>TEMPERATURE RANGE: -40°F to +180°F, -40°C to +82°C</p> <p>PACKAGING: Reels, Coupled Lengths D.O.T. Test Certificate Included with Assemblies. Hose Assemblies Tested/Approved to 7/1/99 D.O.T. Regulations.</p> <p>UL 21 FILE MH 12585 OR UL 21 FILE MH 12585 LISTED/CSA APPROVED (CANADIAN STANDARDS APPROVAL)</p> <ul style="list-style-type: none"> • Meets All Industry Standards <p>PRO SUR FITTINGS AVAILABLE</p> <ul style="list-style-type: none"> • One-Piece Fitting Means No Leak Points
---	---	--

Product Number	Packaging	Nominal I.D.		Nominal O.D.		Reinforcement Spirals	Working Pressure		Min. Bend Radius		Weight	
	Reels (ft.)	(inches)	(mm)	(inches)	(mm)		(psi)	(Mpa)	(inches)	(mm)	(lb/ft)	(Kg/m)
TYPE 75B												
00667304600	700	¼	6.35	0.63	15.88	4	350	2.41	1.50	38.10	0.14	0.22
00667306600	700	⅜	9.53	0.75	19.05	4	350	2.41	2.25	57.15	0.18	0.30
00667308600	700	½	12.70	0.94	23.81	4	350	2.41	3.00	76.20	0.29	0.43
TYPE 75												
22074481662	500-700*	¾	19.05	1.25	31.75	4	350	2.41	4.50	114.30	0.27	0.61
22074641662	300-500*	1	25.40	1.50	38.10	4	350	2.41	7.00	177.80	0.58	0.86